

HECO 2000/2400 BX

Our standard solution for covered transportation of vehicles – appreciated for its unique features among auto sports people around the world. And, in case the standard solution is not suitable, with the flexible modular building system we can create a trailer to meet your specific requirements.

Invest in a HECO you too!



Flat bed

The trailer is built up by aluminium profile extrusions and has a flat surface, i.e. suitable for all sorts of transportation.



Cap

The cover is built up by aluminium sheets glued to a frame of aluminium extrusions.



Axles & Brakes

Steel torsion bogie axles with load equalizer bar and shock absorbers. Mechanical pusher brake system with automatic reverse lock-out function.



Electrical system

13 pole DIN connector on a spiral cord. Dual tail light fittings, reverse- and interior lighting. Position- flash- and brake lights are placed on the upper edge of the cover for best visibility.



Ventilation

Two ventilation gratings placed diagonally.



Wheel tie-downs

Tie-down hooks, movable in T shaped tracks, and four pcs of lashing straps with winch.



Wheel stop

Adjustable aluminium wheel stop and rubber block.



Drive-on ramp

Two pcs of 295 mm wide drive-on ramps in a holder.

Technical data

Model	HECO 2000BX	HECO 2400BX
Flat bed dim.	2,0 x 4,9 m	2,0 x 5,4 m
Inner height	1,5 m	1,65 m
Gross weight	2000 Kg	2400 Kg
Trailer weight	750 Kg	800 Kg
Load capacity	1250 Kg	1600 Kg
OA length/width	6400/2500 mm	6900/2500 mm
Side wall	250 mm	250 mm
Ball&socket gear	50 mm	50 mm
Tyre dim.	175/70 R14	195/70 R14



Accessories

Electro hydraulic lowering

Hydraulic lowering/levelling with electrical pump, battery and power charger.



Electrical winch

Including battery and power charger.



Spare wheel with holder



Theft lock



Spare parts kit

In plastic box.



Aluminium rims

Set of four.



Automatic greasing

Four greasing points.

